

PRATT FLAMMABLE STORAGE CABINET

205L 1 DOOR, ROLLER SET SHELF

PRATT INDOOR FLAMMABLE LIQUID STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD AS1940 "THE STORAGE AND HANDLING OF FLAMMABLE AND COMBUSTIBLE LIQUIDS".

This range of cabinets is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods.

These include flammable liquids such as Paints, Solvents, Petrol, Thinners, Kerosene, Turpentine, White Spirits, Alcohol and Ethanol. Also, combustible liquids such as Diesel, Linseed Oil and Pine Oil.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- Single self closing door with speed adjustable hydraulic closure.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Shelves available to purchase for additional storage (not included). Part Number for shelf is 5560E-29S
- Vertical cabinet accommodates one 205L drum.
- Fixed base roller set, to help move the drum in and out of the cabinet.

- **WEIGHT:** 180kg
- **CAPACITY:** 350L
- **DOORS:** 1

EXTERNAL (MM)			INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1825	865	865	1580	770	775

NOTE:
 1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.
 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.



VOLUME CAPACITY	TOTAL
205L DRUM (44G)	1

Available from



PRATT
SAFETY SYSTEMS

FROM

PARAMOUNT
SAFETY PRODUCTS