

PRATT FLAMMABLE LIQUID STORAGE CABINET: 350L - 1 DOOR - 3 SHELVES

PRATT INDOOR FLAMMABLE LIQUID STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD AS 1940 "THE STORAGE & HANDLING OF FLAMMABLE & COMBUSTIBLE LIQUIDS".

This cabinet is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods. For example: petrol, diesel, paints, solvents, thinners, kerosene, turpentine, white spirits, alcohol and ethanol etc. They are also suitable for the storage of aerosols where additional fire protection is required.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- Single self closing door with speed adjustable hydraulic closure.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.

- **WEIGHT:** 180kg
- **CAPACITY:** 350L
- **DOORS:** 1
- **SHELVES:** 3 (Inc. Base Level)
- **EXTRA SHELF:** 5560E-29S



EXTERNAL (MM)			INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1825	865	865	1580	770	775

NOTE:
1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.
2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	25	75
4L Winchester	16	48
4L Paint Can	12	36
20L Round Can	4	12