

HEARING PROTECTION PYTHON® SLIMLINE NECKBAND EARMUFFS

PRODUCT DATA SHEET: EMPYTNB



PRODUCT CODE:
EMPYTNB



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 4, SLC_{80} 23dB.
- Hearing protection for noise levels to 108dB(A).
- Hi-vis yellow for visual identification.
- Comfortable neckband configuration for extended wear.
- Robust steel wire construction for on-site demands.
- Contemporary low-profile design that withstands abuse without compromising on comfort.
- Solid, lightweight ear cup construction.
- High quality ear cushions & balanced clamping force for comfort.
- Suitable while wearing hard hat.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EMPYTNB	EACH	1	25

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

Order replacement hygiene kit for PRO Python Earmuffs - EMHKPYT.

APPLICATIONS

Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications.



ADJUSTABLE



COMFORT



HI-VIS



HYGIENIC



REUSABLE

PRODUCT DETAILS

Weight:	255g
Clamping Force:	13N
Colour:	Hi-Vis Yellow
Size:	Standard One Size

TEST DATA

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	14.0	16.2	23.1	34.7	29.4	32.9	32.0
Standard Deviation	6.4	5.3	5.4	5.2	5.3	6.3	5.6
Mean-Minus-Standard Deviation Attenuations	7.6	10.9	17.7	29.5	24.1	26.6	26.4

SLC_{80} Value is 23 (Class 4)

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 4, SLC_{80} 23dB

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 108dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMKH25293

Available from



FROM

PARAMOUNT
SAFETY PRODUCTS