

# HEARING PROTECTION PYTHON® SLIMLINE EARMUFFS

PRODUCT DATA SHEET: EMPYTS



PRODUCT CODE:  
EMPYTS



## FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC<sub>80</sub>31dB
- Hearing protection for noise levels to 116dB(A).
- Hi-vis yellow for visual identification.
- High performance & strong durability through steel wire construction for maximum protection.
- Easy adjustment system for individual fit.
- Contemporary low-profile design that withstands abuse without compromising on comfort.
- Solid, lightweight ear cup construction.
- High quality ear cushions, padded foam headband & robust wire construction.
- Low clamping force for comfort.

## AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EMPYTS	EACH	1	25

## CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

Order replacement hygiene kit for PRO Python Earmuffs - EMHKPYT.

## APPLICATIONS

Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications, Insert Applications.



ADJUSTABLE



COMFORT



HI-VIS



HYGIENIC



REUSABLE

## PRODUCT DETAILS

Weight:	280g
Clamping Force:	12.5N
Colour:	Hi-Vis Yellow
Size:	Standard One Size

## TEST DATA

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	18.2	20.5	27.5	40.0	34.7	37.9	37.2
Standard Deviation	2.7	2.8	2.6	3.7	2.2	2.5	3.5
Mean-Minus-Standard Deviation Attenuations	15.5	17.7	24.9	36.3	32.5	35.4	33.7

SLC<sub>80</sub> Value is 31 (Class 5)

## STANDARDS

### CERTIFIED TO:

AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC<sub>80</sub>31dB

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 116dB(A) assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.



AS/NZS1270:2002  
SMKH25293

Available from



FROM

PARAMOUNT  
SAFETY PRODUCTS