

HEARING PROTECTION

PROBELL™ DISPOSABLE EARPLUGS | CORDED & UNCORDED

PRODUCT DATA SHEET: EPYU | EPYC



PRODUCT CODE:
EPYU



PRODUCT CODE:
EPYC



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 27dB.
- Hearing protection for noise levels to 110dB(A).
- Hi-vis yellow for visual identification & compliance.
- Economical & convenient choice for work situations that demand a high degree of comfort, frequent changes or where hygiene presents a problem for re-usage.
- Bell shape provides maximum comfort.
- Design makes it easier to insert & reduces tendency to back out of the ear.
- Pairs packaged in individual poly bags.
- Refill bag compatible with the Pro Choice Safety Gear dispenser station.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EPYU	EACH	1 BOX (200 PAIRS)	10 BOXES (2000 PAIRS)
EPYC	EACH	1 BOX (100 PAIRS)	10 BOXES (1000 PAIRS)

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.



COMFORT



HI-VIS



HYGIENIC

PRODUCT DETAILS

Material:	PU Foam
Length:	2.5cm
Diameter:	1.6cm
Colour:	Hi-Vis Yellow Foam Blue Cord

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	22.9	25.5	29.8	30.0	32.4	40.1	40.1
Standard Deviation	6.5	6.3	7.0	6.8	4.9	6.6	7.0
Mean-Minus-Standard Deviation Attenuations	16.4	19.2	22.8	23.2	27.5	33.5	33.1

SLC₈₀ Value is 27 (Class 5)

APPLICATIONS

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMKH25293

Available from



FROM

