

HEARING PROTECTION

EARPLUG DISPENSER STATION 500 | PROBELL™ DISPOSABLE EARPLUGS REFILL

PRODUCT DATA SHEET: EPDS500A | EPYU500R



PRODUCT CODE:
EPDS500A



PRODUCT CODE:
EPYU500R



FEATURES AND BENEFITS

EPDS500A

- Dispenser holds 500 pairs of ProBullet™ or ProBell™ Disposable Uncorded Earplugs.
- Dispenses one pair at a time.
- Units are sold individually with refills available in 500 pair bags for both ProBullet™ and ProBell™ uncorded™ disposable earplugs

EPYU500R

- 500 uncorded pairs.
- Refill bag compatible with the Pro Choice Safety Gear earplug dispenser station.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EPDS500A	EACH	1	5
EPYU500R	EACH	1 BAG (500 PAIRS)	10 BAGS (5000 PAIRS)

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.

APPLICATIONS

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.



COMFORT



HI-VIS



HYGIENIC

PRODUCT DETAILS

Material:	PU Foam
Length:	2.5cm
Diameter:	1.6cm
Colour:	Hi-Vis Yellow Foam

TEST DATA

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	22.9	25.5	29.8	30.0	32.4	40.1	40.1
Standard Deviation	6.5	6.3	7.0	6.8	4.9	6.6	7.0
Mean-Minus-Standard Deviation Attenuations	16.4	19.2	22.8	23.2	27.5	33.5	33.1

SLC₈₀ Value is 27 (Class 5)

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMKH25293

Available from

