

A close-up photograph of a worker's foot in a tan safety boot with a straight lacing system. The boot is positioned on a concrete surface. In the background, a person is using a power tool, likely a grinder, which is creating a shower of bright orange sparks. The worker is wearing blue socks with a yellow and black pattern. The overall scene is a construction or industrial setting.

LACE UP

NOT DESIGNED FOR THE
STRAIT-LACED WORKER



260050 | Sizes 3-14 (6.5-10.5)

- 200J steel toe cap
- AirZone Comfort System®
- Electrical hazard resistant
- Slip, oil & fat resistant TPU/PU ToughSider sole
- Temperature regulating lining
- OrthoTec Air footbed w/ anatomical arch support
- Coats Nylbond stitching
- Padded tongue and collar
- Premium nubuck leather

Certified to AS 2210.3:2019, ISO 20345:2011, MOD, ASTM F2413



260030 | Sizes 5-14 (6.5-10.5)

- 200J steel toe cap
- AirZone Comfort System®
- Electrical hazard resistant
- Slip, oil & fat resistant TPU/PU ToughSider sole
- Temperature regulating lining
- OrthoTec Air footbed w/ anatomical arch support
- Coats Nylbond stitching
- Padded tongue and collar
- Premium full grain leather

Certified to AS 2210.3:2019, ISO 20345:2011, MOD, ASTM F2413



260020 | Sizes 3-14 (6.5-10.5)

- 200J steel toe cap
- AirZone Comfort System®
- Electrical hazard resistant
- Slip, oil & fat resistant TPU/PU ToughSider sole
- Temperature regulating lining
- OrthoTec Air footbed w/ anatomical arch support
- Coats Nylbond stitching
- Padded tongue and collar
- Premium full grain leather

Certified to AS 2210.3:2019, ISO 20345:2011, MOD, ASTM F2413



550050 | Sizes 5-13 (6.5-10.5)

- 200J steel toe cap
- Heat, oil & acid resistant Vibram® rubber outsole
- Moulded PU scuff cap for longevity
- Antistatic
- SRC slip resistance
- AirZone Comfort System®
- OrthoTec Poron® footbed w/ anatomical arch support
- Dri-Freeze® lining that dissipates heat
- Nomex® vamp stitching
- Silicone AbrasionGuard
- Padded tongue and collar
- Premium nubuck leather

Certified to AS 2210.3:2019, ISO 20345:2011, MOD, ASTM F2413



550020 | Sizes 5-13 (6.5-10.5)

- 200J steel toe cap
- Heat, oil & acid resistant Vibram® rubber outsole
- Moulded PU scuff cap for longevity
- Antistatic
- SRC slip resistance
- AirZone Comfort System®
- OrthoTec Poron® footbed w/ anatomical arch support
- Dri-Freeze® lining that dissipates heat
- Nomex® vamp stitching
- Silicone AbrasionGuard
- Padded tongue and collar
- Premium full grain leather

Certified to AS 2210.3:2019, ISO 20345:2011, MOD, ASTM F2413

