

# HAND PROTECTION ARAX® LITE GLOVE

PRODUCT DATA SHEET: AGND(SIZE)

**PRO**  
PRO CHOICE SAFETY GEAR

PRODUCT CODE:  
AGND(SIZE)



## FEATURES AND BENEFITS

- Certified to EN 420 / AS I NZS2161.2:2005 General Requirements
- Certified to EN 388:2016 Protection Against Mechanical Risks
- EN388:2016 Cut Resistance Level "C".
- Super thin 18 gauge machine knit for comfort & protection.
- Good cut resistance without sacrificing comfort or dexterity.
- Re-inforced nitrile thumb crotch for extra protection where it counts.
- Breathable Arax® liner.
- Form fitting for comfortable all day wear.
- Colour coded cuff for size identification.

## PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	9.3cm +/-	23.0cm +/-
8	9.8cm +/-	24.0cm +/-
9	10.3cm +/-	25.0cm +/-
10	10.8cm +/-	26.0cm +/-
11	11.3cm +/-	27.0cm +/-

## PRODUCT DETAILS

**Material:** Engineered Composite 18 Gauge Seamless Arax® Fibre Liner  
**Dip:** Nitrile Sand Finish in Black with Smooth  
**Palm:** Nitrile Thumb Reinforcing  
**Cuff Type:** Knitted

## APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments. Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying.




## AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
AGND	GREEN	PAIR	12	120

## STANDARDS

CE CATEGORY II:

III Intermediary risk in accordance with:  
 EN 420 / AS I NZS2161.2:2005 General Requirements  
 EN 388:2016 Protection Against Mechanical Risks  
 Results - 4X31C



## CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

Available from



**PRO**  
PRO CHOICE SAFETY GEAR  
FROM  
PARAMOUNT  
SAFETY PRODUCTS