

HAND PROTECTION

ARAX DRY GRIP GLOVES

PRODUCT DATA SHEET: ALD-(SIZE)

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
ALD-(SIZE)



FEATURES AND BENEFITS

- EN388:2016 Cut Resistance Level "D"
- ASTM Cut Level 4
- Contact heat resistant to 100° C
- Good cut resistance without sacrificing comfort or dexterity
- Black latex crinkle dip for superior grip on dry, smooth surfaces
- Breathable Arax® liner
- Form fitting for comfortable all day wear
- Colour coded cuff for size identification
- Anti-static

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut and Abrasion Risks.

PHYSICAL DIMENSIONS

| SIZE | PALM WIDTH | GLOVE LENGTH |
|------|------------|--------------|
| 6 | 7.5cm +/- | 20.5cm +/- |
| 7 | 8.5cm +/- | 21.5cm +/- |
| 8 | 9.5cm +/- | 22.5cm +/- |
| 9 | 10.0cm +/- | 23.5cm +/- |
| 10 | 10.5cm +/- | 24.5cm +/- |
| 11 | 10.5cm +/- | 25.5cm +/- |

AVAILABLE IN

| PRODUCT CODE | QUANTITY | CARTON |
|--------------|----------|-----------|
| ALD-(SIZE) | 12 pairs | 120 pairs |

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

| PERFORMANCE LEVEL | NEWTON | WEIGHT |
|-------------------|------------|--------------|
| A | <2 | 200g |
| B | ≥5 | 500g |
| C | ≥10 | 1kg |
| D | ≥15 | 1.5kg |
| E | ≥22 | 2.2kg |
| F | ≥30 | 3.0kg |

PRODUCT DETAILS

Material: Engineered Composite 13 Gauge Seamless Arax® Fibre Liner
Dip: Latex Crinkle Dip in Black
Cuff Type: Knitted
Colour: Black, Grey
Sizes: 6, 7, 8, 9, 10, 11

STANDARDS

CE CATEGORY:

II Intermediary risks in accordance with:

EN420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2016 Protection Against Mechanical Risks
Results: 4X42D

EN407 AS/NZS 2161.4:1999 Protection Against Thermal Risks
(Heat and Fire)
Results: X1XXXX

ASTM F1 790 Cut Level
Results: 4



Available from



PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS