HAND PROTECTION ARAX WET GRIP GLOVES

PRODUCT DATA SHEET: AND-(SIZE)



PRODUCT CODE: AND-(SIZE)



FEATURES AND BENEFITS

- EN388:2016 Cut Resistance Level "D"
- ASTM Cut Level 4
- Contact heat resistant to 100° C
- Good cut resistance without sacrificing comfort or dexterity
- Nitrile sand finish coated palm
- Breathable Arax® liner
- Form fitting for comfortable all day wear
- Colour coded cuff for size identification
- Anti-static

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to:

Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut and Abrasion Risks.

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	8.5cm +/-	21.5cm +/-
8	9.5cm +/-	22.5cm +/-
9	10.0cm +/-	23.5cm +/-
10	10.5cm +/-	24.5cm +/-
11	10.5cm +/-	25.5cm +/-

AVAILABLE IN

PRODUCT CODE	QUANTITY	CARTON
AND-(SIZE)	12 pairs	120 pairs

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
Α	<2	200g
В	≥5	500g
С	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

PRODUCT DETAILS

Material: Engineered Composite 13 Gauge Seamless Arax® Fibre Liner

Dip: Nitrile Sand Finish in Black

Cuff Type: Knitted
Colour: Black, Grey
Sizes: 7, 8, 9, 10, 11

STANDARDS

CE CATEGORY:

II Intermediary risks in accordance with:

EN420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2016 Protection Against Mechanical Risks

Results: 4X42D

EN407 AS/NZS 2161.4:1999 Protection Against Thermal Risks

(Heat and Fire) Results: X1XXXX







4X42D



