SINGLE DOUBLE LEG WEBBING LANYARD PART CODE: WL01

PRODUCT INFORMATION>

2 Metre Webbing Lanyard WLO1 - Single Leg Webbing Lanyard + Hardware (Refer to Single Leg Lanyard Hardware Page).

PRODUCT FEATURES >

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 150kg, including tools and equipment.
- · Drop forged lanyard hardware.
- Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100 newton (10kg) breaking strength.
- Unique THETA stitch pattern has over 313 stitches resulting in a seam that matches the lanyard's webbing strength, ensuring no weak point in the lanyard assembly.

PRODUCT DETAILS >

- AUS/NZ designed and engineered.
- High Tenacity webbing 28kN, 185% in excess of AS/NZS 1891.5:2020 requirements.
- · Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for wearer of up to 150kg, including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Custom lengths available on request, for example: 1.0m, 1.2m, 1.5m, 1.8m
- Webbing Material: Polyester; 45mm; UV Resilient; Solvent Resistant.
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high strength alloy steel.
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast.
- Web Tenacity: Min 30kN Max 33kN.

STANDARDS >







SINGLE LEG LANYARD HARDWARE

FOR COMPLETE CODE ADD LANYARD & HARDWARE CODE TOGETHER EG. SINGLE LEG WEBBING LANYARD WITH 2 X TRIPLE ACTION KARABINERS = WL01 + KTKT



