



SafetyLink's patented surface mounted FrogLink has set a new benchmark in the field of height safety. This revolutionary all in one unit has been designed to attach to all metal roof profiles with a single row of attachment holes.

- Fast simple unit for installation, fall protection whilst working at heights.
- Low profile reflective design is a plus for any commercial or residential enterprise wanting to maintain an aesthetically pleasing façade.
- Can be fixed to corrugated sheet metal, trimdek, kliplok and a multitude of other metal roof sheeting materials, can be used for domestic or commercial use.
- Dynamic design reduces the load back onto the structure and person attached to the anchor.
- Designed to suit all roof profiles with a single row of attachment holes.
- Install using 7 x 8mm Tri-fold Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range, Aluminium).

WHAT AM I USED FOR?

A surface mounted height safety anchor point for use on metal roof profiles where access to timber is difficult, will arrest from any direction.



STANDARDS

Complies with AS/NZS 1891.4, AS/NZS 5532-2013, EN 795:2012, OSHA 1926.502 and (Plywood – ANSI Z359_18:2017).

Product Code	Description	Weight (kg)	Rated	Material
FROGL001	Surface Mounted Anchor	0.291	15kN	316 Stainless Steel
FROGL001+Rivets	Surface Mounted Anchor + 7 Aluminium Rivets	0.340	15kN	316 Stainless Steel

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



Available from

