

PROWLER



1626401 • Clear Lens



1626402 • Smoke Lens



1626403 • Smoke / Silver Flash Lens



1626404 • Smoke / Blue Flash Lens



1626405 • Green Polarised Lens








25 g

- + HIGH GLOSS, HYDRATED NYLON FRAME FRONT**
- + POLYCARBONATE CO-MOULDED TEMPLE ARMS WITH THERMO PLASTIC RUBBER NOSE PAD & TEMPLE TIPS**
- + EXCEPTIONAL VISUAL CLARITY, 8 BASE CURVE**

bollé
SAFETY

PROWLER

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
PROWLER	 Clear	1626401	I0	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1626402	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke / Silver Flash	1626403	I2	AS/NZS 1337.1.2010	Hard coat
	 Smoke / Blue Flash	1626404	I2	AS/NZS 1337.1.2010	Hard coat
	 Green Polarised	1626405	I3	AS/NZS 1337.1.2010	Hard coat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 2. Range of luminous transmittance 18-43% (flash).
- 3. Range of luminous transmittance 8-18% (smoke & polarised).

APPLICATIONS

- Driving
- Solar UV exposure
- Emergency response
- Rigging
- Assembly and production work

MAIN MARKETS

- Transport
- Mining
- Construction
- Local government and councils
- Utilities: power, gas and water
- Fisheries
- Dental

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lenses: Clear and Smoke
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke, Silver Flash, Blue Flash and Polarised
- Hard coating on Silver, Blue Flash, and Polarised lenses.

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **B-CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	Hydrated Nylon frame front
TEMPLES	PC temple arms + EVA temple
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

Available from



bolle
SAFETY