

VOODOO



1652702 • Smoke Lens



1652705 • Brown Lens



1652707 • Grey/Green Polarised Lens



1652719 • Brown Polarised Lens







28 g

- + TRANSLUCENT POLYCARBONATE FRAME**
- + RUBBER NOSE PADS & EVA TEMPLE TIPS FOR IMPROVED GRIP & COMFORT**
- + ALS ANTI-FOG / ANTI-SCRATCH COATING**
- + UNISEX FIT : MEDIUM / LARGE**

bolle
SAFETY

VOODOO

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
VOODOO	 Smoke	1652702	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Brown	1652705	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Grey/Green Polarised Lens	1652707	I3	AS/NZS 1337.1.2010	Hard Coat
	 Brown Polarised	1652719	I3	AS/NZS 1337.1.2010	Hard Coat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% range 2. (brown).
- 3. Range of luminous transmittance 8 -18% (smoke & polarised).

APPLICATIONS

- Driving
- Solar UV exposure
- Emergency response
- Rigging
- High glare outdoor work places

MAIN MARKETS

- Transport
- Mining
- Construction
- Local government and councils
- Utilities: power, gas and water
- Fisheries

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lenses: Smoke and Brown
- 100% UV 400 – Smoke, Brown and Polarised

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **BOLLÉ CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

Available from



bollé
SAFETY